

## **BROADCAST Series**

Self-powered compact band-pass subwoofer system

# Audio-Performance Broadcast SUB ETZ-amp

The SUB ETZ-amp is a very compact band-pass subwoofer designed to extend the LF frequency range and power bandwidth of Audio Performance Euros, or Zephiros monitor loudspeakers.

The unit contains a 8" long excursion, low distortion, low frequency cone driver mounted in a band-pass enclosure.

The 120 W amplifier module features left and right input for mono applications and stereo left and right HP filtered outputs to feed the Tracios or Zephiros Monitor.

Sensitivity is adjustable to -10dB, 0dB, +4dB. The output level can be set from 0dB to -24dB via a potentiometer. In absence of modulation, a standby device controls electronically the power amplifier and reduces the power consumption to the minimum, the system detects automatically an audio signal and instantaneously restores the power.

The SUB ETZ-amp wood enclosure (birch multiply) is precisely manufactured using the Audio Performance time-proven technique, the outer surface is hard-wearing painted (black, white or any RAL colour).

The aesthetic appeal is not left behind a carefully studied shape with a recessed connectors panel offers the possibility to place the subwoofer on any of it's face.

# **IDEAL FOR**

A/V Production Near Field Monitoring Final on air Mastering Control Sound Effects Spotting Multi Media



**Special Features** 

high efficiency

low distortion

electronically controlled

audio-performance route de cossonay 36c 1040 echallens switzerland



#### **BROADCAST Series**

### **Broadcast SUB ETZ-amp Specifications**

#### Acoustical

 $\begin{array}{l} \mbox{frequency response (1)} \\ 45 - 180 \ Hz \ \pm 3dB \end{array}$ 

max. peak SPL (2) 118dB power amplifier 120 W

crossover frequency 180Hz (active), 24dB per octave

#### **Transducers and electrical**

**LO section** 1 x 8", long excursion, low distortion cone driver.

system nominal impedance electronically balanced 10 kOhms.

Mechanical

finish

rounded edges and corners, the outer surface is hard-wearing painted (black, white or any RAL colour).

connectors IN / OUT (loop) Neutrik XLR 3 pin (1: GND, 2: positive, 3: negative)

others power 3-pin IEC male receptacle 110-230V 100VA

**cabinet size (W x H x D)** 450 x 300 x 385 mm

weight 14 kg

